

В

⇒

Α

Unit Datinga				
Unit Ratings				
Voltage (Line to Line):				
Voltag	e (Line to Neu	tral):		
and Temperature Ratings (Check One): 10		One): 10 seconds	/ 760°C	
		Continuous	/ 385°C	
	0	ther:		
	Ar	mps:		
nclosure Options				
Material and Finish (Check One): Mill Galvanized Steel				З
		ther:		
R		Dne): NEMA 3R/I	P23 (Outdoor)	
IX.	•	ther:	20 (00000)	
Entry (Check One): Bottom Left				
	Ot	her ² :		
Exit (Check One): Bottom Right			ht	
	Ot	her ² :		
ional Components	5			
	- Current Transfo	rmer None		
· · · · ·				
Other (ie 400:5):				
erminal Block for CT Secondary Wiring None				1
	0	ther:		
Dime	ensions			
	sired Sizes ¹			
W (Width)	A (Mounting)	B (Mounting)		
′ x 36" D x 36" H	33"	33"		
′ x 48" D x 48" H	45"	45"		4
′ x 56" D x 56" H	53"	53"	ľ	•
	Other - 3	Other - 3		
Nympic Blvd	DESCRIPTION:			
er, KY USA 41018 : 800.537.6144 /	typical outlin	ne, neutral groundi	na resistor	
859.283.0778 59.283.2978		is, noutrai groundi	19 10010101	
ostglover.com	5/9/06	DRAWN	APPROVED	
DATE: 5/9/06 TORS INC. IT SHEET: 1 OF 1		MAB	DBK	
OR THE	NG NUMBER	1	REVISION	
G #47849,			00	
		1]	

1

1